



TECHNICAL DATA

11DTF50R			
Nominal Diameter	89x64 mm	Voice-Coil Diameter	12 mm
Frequency-Range	4000-20000 Hz	Voice-Coil Winding-Height	2 mm
Impedance	Z 8 Ω	Voice-Coil Former Material	Alu
DC-Resistance	R _E 6 Ω	Flux-Density	1,4 T
Resonant Frequency	F _S 3000 Hz	Magnet-Size	45 mm
		Sensitivity	93 dB/W/m
		Power Capacity, continuous	50 W*
		Power Capacity, 10 ms	100 W*
		Diaphragm Material	Polyester
		Coating	yes

* via crossover

Drive Units 11DTF50R

With the 11DTF50R, we offer a splendid tweeter, having good power capacity and wide field of application, also for the customer conscious of prices. This tweeter may be used for home speakers as well as for high-class car stereo. Being extraordinarily weather-proof and of small size, it recommends itself for mobile installa-

75.

Lautsprecherchassis 11DTF50R

Mit der 11DTF50R bieten wir auch dem preisbewußten Kunden einen hervorragenden Hochtöner mit guter Belastbarkeit und weitem Einsatzbereich. Dieser Hochtöner kann sowohl für Heimlautsprecher als auch für Autoanlagen der Spitzenklasse eingesetzt werden. Die Verwendung in mobilen Anlagen wird durch außerordentliche Klimafestigkeit und kompakte Einbaumaße begünstigt.

FREQUENCY RESPONSE

FFT 3D

