





AIRMT-130

Order No.: 01.3200

EUR 255,00

RRP*

PRODUCTINFOS

Air Motion Transformers

are a special type of tweeter systems which have been developed by the German physicist Oskar Heil during his research on the characteristics of the human ear. The main feature is a film-covered cone with a special folding which vibrates like an accordion when an audio signal is applied. This folding allows to accommodate a large cone area at a minimum of space. The AMTs feature a dynamic sound, an excellent transient response, a high efficiency and a low harmonic distortion.

High-end Air Motion Transformer tweeter, 60 W, 8 Ω

- Tweeter based on the principle of Air Motion Transformer
- High-performance neodymium magnet system
- Fine, dynamic and brilliant reproduction of the high frequencies
- Folded cone made of Kapton and aluminium
- High power capability and high efficiency
- For use from 3,000 Hz on



• Robust aluminium front panel

Klang+Ton 08,09/2016

"AMT of high efficiency for experienced developers."

TECHNICAL SPECIFICATIONS

AIRMT-130

Impedance (Z) 8Ω

Frequency range 2,500-30,000 Hz

Rec. crossov. frequ. (fmax.) (12 dB/oct.) > 3,000 Hz

Power rating 60 W

Peak music power output 120 W

Sensitivity 98 dB/W/m

DC resistance (Re) 5.2 Ω

Magnet diameter neodymium rods

Mounting cutout 71 x 111 mm

Mounting depth 40 mm

Hole spacing X-axis 76 mm

Hole spacing Y-axis 116 mm

Hole spacing Y-axis 116 mm

Dimensions 90 x 130 x 38 mm

Width 90 mm
Height 130 mm
Depth 38 mm
Admiss. ambient temp. 0-40 °C
Weight 0.585 kg

Sales unit 1
Type of speaker AMT

^{*} Important Notice: The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.