



DT-19SU

Order No.: 10.1970

EUR 39,90

RRP *

PRODUCTINFOS

Hi-fi dome tweeter, 50 W, 8 Ω

- 19 mm soft dome, laminate technology
- Double magnet
- Robust plastic front
- Low cone weight
- Optimum brilliance
- For hi-fi applications of high requirements, especially in 3-way systems

TECHNICAL SPECIFICATIONS

DT-19SU

Impedance (Z)

8 Ω

Frequency range

fx-20,000 Hz

DT-19SU

Resonant frequency (fs)	1,500 Hz
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	3,000 Hz
Power rating	50 W
Peak music power output	80 W
Sensitivity	91 dB/W/m
Voice coil diameter	Ø 19 mm
Magnet diameter	Ø 55 mm
Mounting cutout	Ø 66 mm
Mounting depth	33 mm
Dimensions	Ø 100 x 33 mm
Outside diameter	Ø 100 mm
Width	Ø 100 mm
Depth	33 mm
Admiss. ambient temp.	0-40 °C
Weight	0.397 kg
Sales unit	1

* **Important Notice:** The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.