



DT-25N

Order No.: 10.4010

EUR 47,90

RRP *

PRODUCTINFOS

Neodymium hi-fi tweeter, 40 W, 8 Ω

- Outstanding sound characteristics
- Silk soft dome cone with optimised geometry
- Front plate with a specially adapted design
- Very linear reproduction even of lower frequencies
- High efficiency
- Low magnetic dispersion and mechanically very compact due to the application of a high-performance neodymium magnet
- Ideally suited for building smaller speaker systems
- For high-quality standing hi-fi speakersy, e.g. in D'Appolito arrangements
- Very fine and natural sound

TECHNICAL SPECIFICATIONS

DT-25N

Impedance (Z)	8 Ω
Frequency range	fx-20,000 Hz
Resonant frequency (fs)	1,600 Hz
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	2,500 Hz
Power rating	40 W
Peak music power output	80 W
Sensitivity	95 dB/W/m
Voice coil diameter	\varnothing 25 mm
Magnet diameter	\varnothing 46 mm
Mounting cutout	\varnothing 50 mm
Mounting depth	17.7 mm
Dimensions	\varnothing 66 x 21 mm
Outside diameter	\varnothing 66 mm
Width	\varnothing 66 mm
Depth	21 mm
Admiss. ambient temp.	0-40 °C
Weight	65 g
Sales unit	1

* **Important Notice:** The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.