



DT-280

Order No.: 10.3850

EUR 38,90

RRP *

PRODUCTINFOS

Hi-fi soft dome tweeter, 50 W, 8 Ω

- Fine brilliance
- Silk dome of high power capability, 28 mm cone design
- Large cone area for an exceptionally high dynamic power, also with low crossover frequencies
- Elegant, large front plate with anti-reflection coating
- Very wide linear application range of high power capability
- Ideally suited for 2-way combinations of highest quality, also with larger bass-midrange speakers

TECHNICAL SPECIFICATIONS

DT-280

Impedance (Z)	8 Ω
Frequency range	fx-22,000 Hz

DT-280

Resonant frequency (fs)	1,100 Hz
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	2,000 Hz
Power rating	50 W
Peak music power output	100 W
Sensitivity	92 dB/W/m
Voice coil diameter	Ø 28 mm
Magnet diameter	Ø 70 mm
Mounting cutout	Ø 86 mm
Mounting depth	29 mm
Dimensions	Ø 130 x 29 mm
Outside diameter	Ø 130 mm
Width	Ø 130 mm
Depth	29 mm
Admiss. ambient temp.	0-40 °C
Weight	520 g
Sales unit	1

* **Important Notice:** The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.