



DT-28N

Order No.: 10.4020

EUR 57,90

RRP *

PRODUCTINFOS

Neodymium hi-fi tweeter, 50 W, 8 Ω

- Outstanding sound characteristics
- Very linear reproduction even of lower frequencies
- High efficiency
- 28 mm extra efficient silk cone
- Perfectly small front plate for high-performance speaker systems of the smallest size possible
- Mounting into perfect D'Appolito arrangements also in lying centres due to low magnetic dispersion

TECHNICAL SPECIFICATIONS

DT-28N

Impedance (Z)

8 Ω

Frequency range

fx-20,000 Hz

DT-28N

Resonant frequency (fs)	1,200 Hz
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	2,000 Hz
Power rating	50 W
Peak music power output	100 W
Sensitivity	94 dB/W/m
Voice coil diameter	Ø 28 mm
Magnet diameter	Ø 46 mm
Mounting cutout	Ø 50 mm
Mounting depth	16.7 mm
Dimensions	55 x 55 x 20 mm
Width	-
Height	-
Depth	-
Admiss. ambient temp.	0-40 °C
Weight	74 g
Sales unit	1

* **Important Notice:** The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.