



DT-352NF

Order No.: 10.5900

EUR 89,90

RRP *

PRODUCTINFOS

Hi-fi dome tweeter, 80 W, 8 Ω

- 25 mm (1") metal dome, finest resolution of the high frequency range
- No ferrofluid in the air gap of the drive system
- Special light metal alloy without resonance behaviour typical for metal
- Double magnet system with drilled pole core
- Damped coupling volume for a low resonant frequency
- For use with a crossover frequency from 1,500 Hz on via 18 dB filter
- Very wide radiation range, goes beyond 25 kHz

TECHNICAL SPECIFICATIONS

DT-352NF

Impedance (Z)

8 Ω

DT-352NF

Frequency range	fx-25,000 Hz
Resonant frequency (fs)	800 Hz
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	2,000 Hz/1,500 Hz (18 dB)
Power rating	80 W
Peak music power output	150 W
Sensitivity	91 dB/W/m
Voice coil diameter	Ø 25 mm
Magnet diameter	Ø 72 mm
Mounting cutout	Ø 87 mm
Mounting depth	42 mm
Mounting hole diameter	Ø 98 mm
Hole spacing X-axis	69.3 mm
Hole spacing Y-axis	69.3 mm
Dimensions	Ø 110 x 46 mm
Outside diameter	Ø 110 mm
Width	Ø 110 mm
Depth	46 mm
Admiss. ambient temp.	0-40 °C
Weight	0.75 kg
Sales unit	1

* **Important Notice:** The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.