



## HT-88

Order No.: 10.3170

**EUR 27,90**

RRP \*

### PRODUCTINFOS

**PA horn tweeter, 50 W, 8  $\Omega$**

- Very linear and wide bandwidth radiation
- High efficiency
- Ferrofluid-cooled and ferrofluid-vaporised

### TECHNICAL SPECIFICATIONS

#### HT-88

Impedance (Z)	8 $\Omega$
Frequency range	fx-18 kHz
Resonant frequency (fs)	2.5 kHz
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	4 kHz
Power rating	50 W

**HT-88**

Peak music power output	100 W
Sensitivity	99 dB/W/m
Voice coil diameter	Ø 25 mm
Magnet diameter	Ø 80 mm
Mounting cutout	Ø 82 mm
Mounting depth	75 mm
Hole spacing X-axis	67 mm
Hole spacing Y-axis	67 mm
Dimensions	87 x 87 x 75 mm
Width	87 mm
Height	87 mm
Depth	75 mm
Admiss. ambient temp.	0-40 °C
Weight	670 g
Sales unit	1

\* **Important Notice:** The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.