



RBT-1000

Order No.: 10.1610

EUR 119,90

RRP *

PRODUCTINFOS

Ribbon tweeter for PA and hi-fi, 40 W, 6 Ω

- Magnetostatic speaker with waveguide
- Tweeter system from the L-RAY/1000
- Fine and brilliant reproduction of the high range
- For use from 3,000 Hz (hi-fi) or 4,000 Hz (PA) on via 18 dB filter
- Diecast aluminium horn front attachment, neodymium magnet
- Vertical or horizontal mounting possible due to square front panel

TECHNICAL SPECIFICATIONS

RBT-1000

Impedance (Z)

6Ω

Frequency range

fx-22,000 Hz



RBT-1000

Resonant frequency (fs) 1.6 kHz

Rec. crossov. frequ. (fmax.) (12 dB/oct.) > 2,500 Hz

Power rating 40 W

Peak music power output 80 W

Sensitivity 96 dB/W/m

Magnet diameter magnetostatic speaker

Mounting cutout 94 x 94 mm

Mounting depth 34 mm
Hole spacing X-axis 87 mm
Hole spacing Y-axis 87 mm

Dimensions 104 x 104 x 24 mm

Width 104 mm
Height 104 mm
Depth 24 mm
Admiss. ambient temp. 0-40 °C
Weight 237 g
Sales unit 1

^{*} Important Notice: The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.