



RBT-95

Order No.: 10.2250

EUR 72,90

RRP *

PRODUCTINFOS

Ribbon tweeter, 30 W, 8 Ω

- Magnetostatic speakers of a high efficiency
- Perfectly fine dynamic reproduction of the high range and the brilliance frequency range
- Power capability of the system can considerably be increased by voltage dividers and maybe higher crossover frequencies (level attenuations which take tweeters to the level of normal hi-fi systems)
- Very light sound of low distortion which particularly improves the stereophony in applications from 5 kHz on
- By adding a super tweeter above 8-10 kHz, e.g. even high-quality full range systems can be further improved

TECHNICAL SPECIFICATIONS

RBT-95

Impedance (Z)

8 Ω

RBT-95

Frequency range	fx-22,000 Hz
Resonant frequency (fs)	4,500 Hz
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	5,000 Hz
Power rating	30 W
Peak music power output	60 W
Sensitivity	98 dB/W/m
Magnet diameter	magnetostatic speaker
Mounting cutout	80 x 45 mm
Mounting depth	17 mm
Hole spacing X-axis	
Hole spacing Y-axis	
Dimensions	Ø 95 x 17 mm
Outside diameter	
Width	
Depth	
Admiss. ambient temp.	
Weight	110 g
Sales unit	

* **Important Notice:** The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.