



SP-155X

Order No.: 10.1360

EUR 59,90

RRP *

PRODUCTINFOS

Full range speaker, 25 W, 8 Ω

- Dual cone
- Very wide bandwidth and linear reproduction
- High efficiency
- For any PA application up to hi-fi

TECHNICAL SPECIFICATIONS

SP-155X

Impedance (Z)	8 Ω
Frequency range	f3-20,000 Hz
Resonant frequency (fs)	70 Hz
Power rating	25 W

SP-155X

Peak music power output	50 W
Sensitivity	93 dB/W/m
Suspension compl. (Cms)	0.75 mm/H
Moving mass (Mms)	6.5 g
Mech. Q factor (Qms)	2.87
Electr. Q factor (Qes)	0.88
Total Q factor (Qts)	0.67
Equivalent volume (Vas)	14 l
DC resistance (Re)	6.5 Ω
Force factor (BxL)	4.6 Tm
Voice coil induct. (Le)	0.4 mH
Voice coil diameter	\varnothing 25.5 mm
Voice coil former	aluminium
Linear excursion (X_{MAX})	\pm 1 mm
Eff. cone area (Sd)	117 cm ²
Magnet weight	380 g
Magnet diameter	\varnothing 100 mm
Mounting cutout	\varnothing 146mm
Mounting depth	69 mm
Mounting hole diameter	\varnothing 158 mm
Hole spacing X-axis	111 mm
Hole spacing Y-axis	111 mm
Dimensions	\varnothing 155 mm x 75 mm
Outside diameter	\varnothing 170 mm
Width	\varnothing 155 mm
Depth	75 mm
Admiss. ambient temp.	0-40 °C
Weight	1.14 kg
Sales unit	1
Type of speaker	

* **Important Notice:** The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.