



SP-200X

Order No.: 10.0400

EUR 77,90

RRP *

PRODUCTINFOS

Hi-fi full range speaker, 35 W, 8 Ω

- One-piece rubber gasket
- Very good linearity
- High efficiency
- For PA systems of special sound requirements or in large column speakers

HOBBY HiFi 01/2012

"The SPH-200X impresses with an excellent sound quality."

TECHNICAL SPECIFICATIONS

SP-200X

Impedance (Z)	8 Ω
Frequency range	f3-15,000 Hz
Resonant frequency (fs)	50 Hz
Power rating	35 W
Peak music power output	70 W
Sensitivity	92 dB/W/m
Suspension compl. (Cms)	0.77 mm/N
Moving mass (Mms)	11.5 g
Mech. Q factor (Qms)	1.96
Electr. Q factor (Qes)	0.7
Total Q factor (Qts)	0.52
Equivalent volume (Vas)	48 l
DC resistance (Re)	7.2 Ω
Force factor (BxL)	6.1 Tm
Voice coil induct. (Le)	0.3 mH
Voice coil diameter	\varnothing 25.5 mm
Voice coil former	aluminium
Linear excursion (X _{MAX})	\pm 1.6 mm
Eff. cone area (Sd)	210 cm ²
Magnet weight	500 g
Magnet diameter	\varnothing 100 mm
Mounting cutout	\varnothing 188 mm
Mounting depth	72 mm
Dimensions	\varnothing 205 mm x 80 mm
Outside diameter	\varnothing 205 mm
Width	\varnothing 205 mm
Depth	80 mm
Admiss. ambient temp.	0-40 °C
Weight	1.35 kg
Sales unit	1
Type of speaker	

* **Important Notice:** The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.