



## SP-30

Order No.: 10.1530

**EUR 19,90**

RRP \*

### PRODUCTINFOS

**Universal speaker, 5 W, 4  $\Omega$**

- Dual cone
- Wide frequency response
- For general applications from car speakers to column speakers

### TECHNICAL SPECIFICATIONS

#### SP-30

Impedance (Z)	4 $\Omega$
Frequency range	f3-15,000 Hz
Resonant frequency (fs)	150 Hz
Power rating	5 W
Peak music power output	10 W

**SP-30**

Sensitivity	88 dB/W/m
Suspension compl. (Cms)	0.52 mm/N
Moving mass (Mms)	1.7 g
Mech. Q factor (Qms)	2.5
Electr. Q factor (Qes)	1.04
Total Q factor (Qts)	0.73
Equivalent volume (Vas)	0.7 l
DC resistance (Re)	3.5 $\Omega$
Force factor (BxL)	2.33 Tm
Voice coil induct. (Le)	0.18 mH
Voice coil diameter	20 mm
Voice coil former	aluminium
Linear excursion ( $X_{MAX}$ )	$\pm 1.5$ mm
Eff. cone area (Sd)	31 cm <sup>2</sup>
Magnet weight	150 g
Magnet diameter	$\varnothing 60$ mm
Mounting cutout	$\varnothing 73$ mm
Mounting depth	37.5 mm
Dimensions	78 x 78 x 40 mm
Width	78 mm
Height	78 mm
Depth	40 mm
Admiss. ambient temp.	0-40 °C
Weight	0.3 kg

\* **Important Notice:** The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.