



## SP-40

Order No.: 10.0670

**EUR 23,90**

RRP \*

### PRODUCTINFOS

**Universal speaker, 8 W, 8  $\Omega$**

- Inverse surround
- Plastic dust cap
- Good radiation quality
- Wide frequency response
- High mechanical capability

### TECHNICAL SPECIFICATIONS

#### SP-40

Impedance (Z)	8 $\Omega$
Frequency range	f3-10,000 Hz
Resonant frequency (fs)	80 Hz

**SP-40**

Power rating	8 W
Peak music power output	16 W
Sensitivity	86 dB/W/m
Suspension compl. (Cms)	0.62 mm/N
Moving mass (Mms)	5.7 g
Mech. Q factor (Qms)	2.5
Electr. Q factor (Qes)	0.97
Total Q factor (Qts)	0.7
Equivalent volume (Vas)	2.6 l
DC resistance (Re)	6.5 $\Omega$
Force factor (BxL)	4.33 Tm
Voice coil induct. (Le)	0.2 mH
Voice coil diameter	$\varnothing$ 25.5 mm
Voice coil former	aluminium
Linear excursion ( $X_{MAX}$ )	$\pm$ 2 mm
Eff. cone area (Sd)	55 cm <sup>2</sup>
Magnet weight	150 g
Magnet diameter	$\varnothing$ 70 mm
Mounting cutout	$\varnothing$ 95 mm
Mounting depth	51 mm
Dimensions	103 x 103 x 55 mm
Width	103 mm
Height	103 mm
Depth	55 mm
Admiss. ambient temp.	0-40 °C
Weight	0.46 kg
Sales unit	1
Type of speaker	

\* **Important Notice:** The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.