



SPH-30X/4SW

Order No.: 10.4180

EUR 77,90

RRP *

PRODUCTINFOS

High-quality hi-fi full range speakers, 20 W, 8 Ω (/8) or 4 Ω (/4), with black Kevlar cone

- Well-damped Kevlar cone of extra low weight
- Drive system with full air ventilation
- High-quality NEODYMIUM magnet system with double magnet
- Specially developed basket also for multiple arrangements
- High efficiency
- Small speakers for background PA applications or e.g. rear speakers in home cinema systems
- Suitable for applications from mid-high range speakers or full range midrange speakers in high-end hi-fi speaker systems to multiple arrangements in column speakers

TECHNICAL SPECIFICATIONS

SPH-30X/4SW

Impedance (Z)

4 Ω

SPH-30X/4SW

Frequency range	f3-17,000 Hz
Resonant frequency (fs)	105 Hz
Power rating	20 W
Peak music power output	50 W
Sensitivity	87 dB/W/m
Suspension compl. (Cms)	0.84 mm/N
Moving mass (Mms)	2.63 g
Mech. Q factor (Qms)	9.35
Electr. Q factor (Qes)	0.39
Total Q factor (Qts)	0.42
Equivalent volume (Vas)	1.06 l
DC resistance (Re)	3.55 Ω
Force factor (BxL)	3.91 Tm
Voice coil induct. (Le)	0.5 mH
Voice coil diameter	Ø 21 mm
Voice coil former	Kapton
Linear excursion (X _{MAX})	± 2 mm
Eff. cone area (Sd)	30 cm ²
Magnet weight	neodymium
Mounting cutout	Ø 73 mm
Mounting depth	40.7 mm
Dimensions	80.5 mm x 42 mm
Width	80.5 mm
Height	80.5 mm
Depth	42 mm
Admiss. ambient temp.	0-40 °C
Weight	143 g
Sales unit	1
Type of speaker	3"

* **Important Notice:** The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.