



SPH-60X

Order No.: 10.0920

EUR 47,90

RRP *

PRODUCTINFOS

Full range speaker, 30 W, 8 Ω

- Drilled pole core
- Very good frequency response linearity also in the high frequency range
- For general applications
- Speaker from the successful building concepts CT193 and CT194 of the magazine Klang+Ton

TECHNICAL SPECIFICATIONS

SPH-60X

Impedance (Z) 8Ω

Frequency range f3-20,000 Hz

Resonant frequency (fs) 60 Hz Power rating 30 W



SPH-60X

60 W Peak music power output

89 dB/W/m Sensitivity

Suspension compl. (Cms) 1.19 mm/N

Moving mass (Mms) 5.9 g

2.17 Mech. Q factor (Qms)

Electr. Q factor (Qes) 0.53

Total Q factor (Qts) 0.42

9 I Equivalent volume (Vas)

DC resistance (Re) 6.2 Ω

5.1 Tm Force factor (BxL)

Voice coil induct. (Le) 0.4 mH

Voice coil diameter Ø 25.5 mm

Voice coil former aluminium

Linear excursion (X_{MAX}) ± 1.3 mm

Eff. cone area (Sd) 80 cm²

Magnet weight 370 g

Magnet diameter Ø 100 mm

Mounting cutout Ø 122 mm Mounting depth 70 mm

Dimensions 130 x 130 x 71 mm

Width 130 mm 130 mm Height Depth 71 mm 0-40 °C Admiss. ambient temp.

Weight 1.1 kg

Sales unit 1 5"

Type of speaker

^{*} Important Notice: The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.