



SPH-68X/AD

Order No.: 10.1390

EUR 54,90

RRP *

PRODUCTINFOS

Full range speaker, 30 W, 8 Ω

- Drilled pole core
- Flat wire voice coil
- Very good frequency response linearity also in the high frequency range
- For general applications

TECHNICAL SPECIFICATIONS

SPH-68X/AD

Impedance (Z)	8 Ω
Frequency range	f3- 20,000 Hz
Resonant frequency (fs)	60 Hz
Power rating	30 W

SPH-68X/AD

Peak music power output	60 W
Sensitivity	89 dB/W/m
Suspension compl. (Cms)	1.1 mm/N
Moving mass (Mms)	6.5 g
Mech. Q factor (Qms)	3.19
Electr. Q factor (Qes)	0.49
Total Q factor (Qts)	0.43
Equivalent volume (Vas)	9.7 l
DC resistance (Re)	6.5 Ω
Force factor (BxL)	5.7 Tm
Voice coil induct. (Le)	0.5 mH
Voice coil diameter	25.5 mm
Voice coil former	Kapton
Linear excursion (X_{MAX})	± 1 mm
Eff. cone area (Sd)	80 cm ²
Magnet weight	370 g
Magnet diameter	\varnothing 100 mm
Mounting cutout	\varnothing 122 mm
Mounting depth	70 mm
Dimensions	130 x 130 x 71 mm
Width	130 mm
Height	130 mm
Depth	71 mm
Admiss. ambient temp.	0-40 °C
Weight	1.1 kg
Sales unit	1
Type of speaker	5"

* **Important Notice:** The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.