



SPM-200X/4

Order No.: 10.5370

EUR 25,90

RRP *

PRODUCTINFOS

Full range speaker, 30 W, 4 Ω

- Sheet steel basket
- Paper cone with dual cone
- Wide frequency response
- High efficiency
- For PA and hi-fi applications
- Subwoofer support required for hi-fi applications

TECHNICAL SPECIFICATIONS

SPM-200X/4

Impedance (Z)

4 Ω

Frequency range

f3-15,000 Hz

SPM-200X/4

Resonant frequency (fs)	89 Hz
Power rating	30 W
Peak music power output	60 W
Sensitivity	94 dB/W/m
Suspension compl. (Cms)	0.27 mm/N
Moving mass (Mms)	9.9 g
Mech. Q factor (Qms)	2.69
Electr. Q factor (Qes)	1.52
Total Q factor (Qts)	0.97
Equivalent volume (Vas)	14.9 l
DC resistance (Re)	3.7 Ω
Force factor (BxL)	3.9 Tm
Voice coil induct. (Le)	0.2 mH
Voice coil diameter	\varnothing 25 mm
Voice coil former	aluminium
Linear excursion (X_{MAX})	\pm 1 mm
Eff. cone area (Sd)	201 cm ²
Magnet weight	229 g
Magnet diameter	\varnothing 70 mm
Mounting cutout	\varnothing 184 mm
Mounting depth	76 mm
Mounting hole diameter	\varnothing 194 mm
Dimensions	\varnothing 205 mm x 82 mm
Outside diameter	\varnothing 205 mm
Width	\varnothing 205 mm
Depth	82 mm
Admiss. ambient temp.	0-40 °C
Weight	0.734 kg
Sales unit	1
Type of speaker	-

* **Important Notice:** The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.