



SPM-205/4

Order No.: 10.5380

Price upon request

PRODUCTINFOS

Hi-fi bass-midrange speakers, 70 W, 8 Ω (/8) and 4 Ω (/4)

- Excellent replacement speakers of the same quality as from the original equipment manufacturer
- Coated low-resonance paper cone
- Long-term stable rubber surround
- To be used preferably in closed or transmission line cabinets

TECHNICAL SPECIFICATIONS

SPM-205/4

Impedance (Z)	4 Ω
Frequency range	f3-5,000 Hz
Resonant frequency (fs)	37 Hz
Power rating	70 W
Peak music power output	150 W
Sensitivity	89 dB/W/m

SPM-205/4

Suspension compl. (Cms)	0.98 mm/H
Moving mass (Mms)	18 g
Mech. Q factor (Qms)	2.71
Electr. Q factor (Qes)	0.68
Total Q factor (Qts)	0.55
Equivalent volume (Vas)	72 l
DC resistance (Re)	3.6 Ω
Force factor (BxL)	4.75 Tm
Voice coil induct. (Le)	0.65 mH
Voice coil diameter	\varnothing 25.5 mm
Voice coil former	aluminium
Linear excursion (X_{MAX})	\pm 3 mm
Eff. cone area (Sd)	210 cm ²
Magnet weight	380 g
Magnet diameter	\varnothing 80 mm
Mounting cutout	\varnothing 183 mm
Mounting depth	80 mm
Mounting hole diameter	\varnothing 216 mm
Dimensions	\varnothing 200 mm x 88 mm
Outside diameter	\varnothing 200 mm
Width	\varnothing 200 mm
Depth	88 mm
Admiss. ambient temp.	0-40 °C
Weight	1.062 kg
Packing unit	1
Type of speaker	8"