



SPP-125

Order No.: 10.1070

Price upon request

PRODUCTINFOS

Midrange speaker, 22 W, 8 Ω

Closed basket, no further midrange cabinet required.

This series of speakers with polypropylene cone is very well-suited for replacing defective 8 Ω speakers in hi-fi speaker systems.

TECHNICAL SPECIFICATIONS

SPP-125

Impedance (Z)	8 Ω
Frequency range	800-8,000 Hz
Resonant frequency (fs)	550 Hz
Power rating	22 W
Peak music power output	45 W
Sensitivity	92 dB/W/m

SPP-125

DC resistance (Re)	6.5 Ω
Voice coil induct. (Le)	0.2 mH
Voice coil diameter	\varnothing 20 mm
Voice coil former	aluminium
Eff. cone area (Sd)	73 cm ²
Magnet weight	150 g
Magnet diameter	\varnothing 70 mm
Mounting cutout	\varnothing 110 mm
Mounting depth	43 mm
Mounting hole diameter	\varnothing 122 mm
Hole spacing X-axis	86 mm
Hole spacing Y-axis	86 mm
Dimensions	\varnothing 131 mm x 50 mm
Outside diameter	\varnothing 131 mm
Width	\varnothing 131 mm
Depth	50 mm
Admiss. ambient temp.	0-40 °C
Weight	0.472 kg
Packing unit	1
Type of speaker	5"