



SPP-90

Order No.: 10.1150

EUR 20,90

RRP*

PRODUCTINFOS

Tweeter, 22 W, 8 Ω

- Low crossover frequency possible
- Closed basket

This series of speakers with polypropylene cone is very well-suited for replacing defective 8 Ω speakers in hifi speaker systems.

TECHNICAL SPECIFICATIONS

SPP-90

Impedance (Z) 8 Ω

Frequency range 2,000-18,000 Hz

Resonant frequency (fs) 1,000 Hz



SPP-90

Power rating 22 W Peak music power output 45 W

Sensitivity 92 dB/W/m

DC resistance (Re) $6.5~\Omega$ Voice coil induct. (Le) 0.1~mH Voice coil diameter Ø 15 mm Voice coil former aluminium

Eff. cone area (Sd) 23 cm²

Magnet weight 85 g

Magnet diameter Ø 60 mm

Mounting cutout Ø 61 mm

Mounting depth 25.7 mm

Dimensions Ø 78 mm x 30 mm

Outside diameter Ø 78 mm

Width Ø 78 mm

Depth 30 mm

Admiss. ambient temp. 0-40 °C

Weight 0.23 kg

Sales unit 1

Type of speaker 3"

^{*} Important Notice: The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.