



SPX-20M

Order No.: 10.0930

EUR 62,90

RRP *

PRODUCTINFOS

Miniature hi-fi full range speaker, 15 W, 8 Ω

- Round steel basket with rear-ventilated centering spider
- Adhesive mounting or clamp mounting
- Inverse laminated cone
- Efficient neodymium drive system
- Perfect full range reproduction with an excellent efficiency in relation to its size
- 25 mm voice coil of high power capability

TECHNICAL SPECIFICATIONS

SPX-20M

Impedance (Z)

8 Ω

Frequency range

f3-22,000 Hz

SPX-20M

Resonant frequency (fs)	157 Hz
Power rating	15 W
Peak music power output	30 W
Sensitivity	87 dB/W/m
Suspension compl. (Cms)	0.76 mm/N
Moving mass (Mms)	1.3 g
Mech. Q factor (Qms)	4.52
Electr. Q factor (Qes)	0.46
Total Q factor (Qts)	0.42
Equivalent volume (Vas)	0.2 l
DC resistance (Re)	6.9 Ω
Force factor (BxL)	4.5 Tm
Voice coil induct. (Le)	0.13 mH
Voice coil diameter	\varnothing 25 mm
Voice coil former	Kapton
Linear excursion (X_{MAX})	\pm 0.5 mm
Eff. cone area (Sd)	13 cm ²
Magnet weight	neodymium
Magnet diameter	\varnothing 39 mm
Mounting cutout	\varnothing 51.5 mm
Mounting depth	33.5 mm
Dimensions	\varnothing 57 mm x 37.5 mm
Outside diameter	\varnothing 57 mm
Width	-
Depth	-
Admiss. ambient temp.	0-40 °C
Weight	0.17 kg
Sales unit	1
Type of speaker	-

* **Important Notice:** The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.