



## SPX-30M

Order No.: 10.1650

**EUR 28,90**

RRP \*

### PRODUCTINFOS

**Hi-fi full range speaker, 20 W, 8  $\Omega$**

- Excellent sound quality
- Low-resonance polypropylene cone
- Rear-ventilated centering spider
- Magnet system with shielding
- Application in small speakers or satellite systems
- Ideally suited for application in FAST speakers (full range and subwoofer technology)

### HOBBY HiFi 03/2012

"Without a correction circuit, reaches its full potential ... an excellent 3" full range speaker available at an amazingly attractive price."

## TECHNICAL SPECIFICATIONS

### SPX-30M

|                                |                             |
|--------------------------------|-----------------------------|
| Impedance (Z)                  | 8 $\Omega$                  |
| Frequency range                | f3-20,000 Hz                |
| Resonant frequency (fs)        | 100 Hz                      |
| Power rating                   | 20 W                        |
| Peak music power output        | 40 W                        |
| Sensitivity                    | 86 dB/W/m                   |
| Suspension compl. (Cms)        | 1.23 mm/N                   |
| Moving mass (Mms)              | 2.1 g                       |
| Mech. Q factor (Qms)           | 3.453                       |
| Electr. Q factor (Qes)         | 0.89                        |
| Total Q factor (Qts)           | 0.71                        |
| Equivalent volume (Vas)        | 1.78 l                      |
| DC resistance (Re)             | 6.4 $\Omega$                |
| Force factor (BxL)             | 3.05 Tm                     |
| Voice coil induct. (Le)        | 0.18 mH                     |
| Voice coil diameter            | $\varnothing$ 20 mm         |
| Voice coil former              | Kapton                      |
| Linear excursion ( $X_{MAX}$ ) | $\pm$ 1.1 mm                |
| Eff. cone area (Sd)            | 32 cm <sup>2</sup>          |
| Magnet weight                  | 119 g                       |
| Magnet diameter                | $\varnothing$ 68 mm         |
| Mounting cutout                | $\varnothing$ 71 mm         |
| Mounting depth                 | 53 mm                       |
| Dimensions                     | $\varnothing$ 93 mm x 55 mm |
| Outside diameter               | $\varnothing$ 93 mm         |
| Width                          | $\varnothing$ 93 mm         |
| Depth                          | 55 mm                       |
| Admiss. ambient temp.          | 0-40 °C                     |
| Weight                         | 0.5 kg                      |
| Sales unit                     | 1                           |
| Type of speaker                | 3"                          |

\* **Important Notice:** The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.