



SPX-32M

Order No.: 10.0940

EUR 30,90

RRP *

PRODUCTINFOS

Hi-fi full range speaker, 20 W, 8 Ω

- Excellent sound quality
- High-quality paper cone
- Wooden phase plug for optimising radiation pattern
- Rear-ventilated centering spider
- Magnet system with shielding
- Application in small speakers or satellite systems
- Ideally suited for application in FAST speakers (full range and subwoofer technology)

HOBBY HiFi 03/2012

"Audiophile characteristics due to paper cone and solid wooden phase plug."

TECHNICAL SPECIFICATIONS

SPX-32M

Impedance (Z)	8 Ω
Frequency range	f3-22,000 Hz
Resonant frequency (fs)	110 Hz
Power rating	20 W
Peak music power output	40 W
Sensitivity	88 dB/W/m
Suspension compl. (Cms)	1.11 mm/N
Moving mass (Mms)	1.7 g
Mech. Q factor (Qms)	7.66
Electr. Q factor (Qes)	0.60
Total Q factor (Qts)	0.56
Equivalent volume (Vas)	1.6 l
DC resistance (Re)	6.6 Ω
Force factor (BxL)	3.69 Tm
Voice coil induct. (Le)	0.18 mH
Voice coil diameter	\varnothing 20 mm
Voice coil former	Kapton
Linear excursion (X_{MAX})	\pm 1.1 mm
Eff. cone area (Sd)	32 cm ²
Magnet weight	99 g
Magnet diameter	\varnothing 68 mm
Mounting cutout	\varnothing 71 mm
Mounting depth	52.5 mm
Dimensions	\varnothing 93 mm x 55 mm
Outside diameter	\varnothing 93 mm
Width	\varnothing 93 mm
Depth	55 mm
Admiss. ambient temp.	0-40 °C
Weight	0.498 kg
Sales unit	1
Type of speaker	3"

* **Important Notice:** The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.