

Model Number: DX20BF00-08  
Product Line: Peerless Gold

Revision: Rev 3\_0  
Date: 7-Mar-13




**Product Description:**

This DX family tweeter features a 8 Ω 19 mm voice coil, a damped silk diaphragm with large surround roll to produce a low resonant frequency, and a ferrite magnet motor which adds heat sinking for power handling capacity. The faceplate features recessed mounting holes to minimize reflections.



**Mechanical 2D Drawing:**



**Specifications:**

DC Resistance	$R_{evc}$	Ω	7.5	±7.5%	Energy Bandwidth Product	EBP	$(1/Q_{es}) \cdot f_s$	191
Minimum Impedance	$Z_{min}$	Ω	8.3	±7.5%	Moving Mass	$M_{ms}$	g	0.12
Voice Coil Inductance	$L_e$	mH	0.02		Suspension Compliance	$C_{ms}$	um/N	310.0
Resonant Frequency	$f_s$	Hz	810	±20%	Effective Cone Diameter	D	cm	2.5
Mechanical Q Factor	$Q_{ms}$	-	2.9		Effective Piston Area	$S_D$	cm <sup>2</sup>	4.9
Electrical Q Factor	$Q_{es}$	-	4.23		Equivalent Volume	$V_{as}$	L	0.011
Total Q Factor	$Q_{ts}$	-	1.71		Motor Force Factor	BL	T-m	1.06
Ratio $f_s / Q_{es}$	F	$f_s / Q_{es}$	474		Motor Efficiency Factor	$\beta$	$(T \cdot m^2) / \Omega$	0.15
Half Space Sensitivity @ 2.83V	$dB @ 2.83V/1m$	dB	86.1	±1.0 <sup>1</sup>	Voice Coil Former Material	$VC_m$	-	ASV
Sensitivity @ 1W/1m	$1W/1m$	dB	85.8	±1.0 <sup>1</sup>	Voice Coil Inner Diameter	$VC_d$	mm	19.30
					Gap Height	Gh	mm	2.00
Rated Noise Power (IEC 2685 18.1)	P	W	60		Maximum Linear Excursion	$X_{max}$	mm	0.10
Test Spectrum Bandwidth	2.5KHz-20KHz	12 dB/Oct			Ferrofluid Type	FF	-	APG027N
					Transducer Size	-	-	19 mm
					Transducer Mass	-	Kg	0.169

1 - Piston Band Sensitivity Tolerance

**Frequency and Impedance Response:**

